

American AVK Fire Hydrants



- Meets or exceeds AWWA C502 Standard
- UL Listed and FM approved
- Ductile Iron construction
- 250 psi rated
- Lowest number of parts for ease of maintenance.
- Ten-Year Warranty.

Revolutionary One-Piece Main Valve

- EPDM rubber encapsulated ductile Iron main valves
- Replaces the traditional 13 piece main valve with one part construction.
- Stainless steel holding pin, for ease of removal and maintenance.
- Cost effective when compared to traditional main valve design.
- Replacement refitted in minutes, saving valuable maintenance time.
- Extra deep and wide drain/seat ring channel for fast effective draining.



- Pumper and Hose nozzles have quarter turn twist lock design for easy in field removal.
- Stainless steel traffic breakaway coupling.
- Weather shield is standard.
- Top lubrication, using either oil or grease, no disassembles required.
- Fusion bonded epoxy coated internally and externally.
- Hydrant body will rotate 360 degrees by loosening four (4) bolts.
- Ductile iron inlet shoe replaceable without dismantling hydrant.
- Same gasket used for bonnet and traffic flange.

[American AVK Company](#)

5286 E. Home Ave. Fresno, CA 93727. Telephone: 559-452-4300 – Fax: 559-452-4349