TUBING & CONNECTORS ELOMO



PERISTALTIC PUMP TUBING AND CONNECTION FITTINGS

COMPATIBLE **WITH MANY PERISTALTIC**

Designed to meet the demanding requirements of chemical injection and dispensing applications

FLOMOTION Pump Tubing and Connection Fittings for peristaltic hose and diaphragm pumps are specially designed for long life and leakproof, trouble-free operation. Peristaltic connectors are color-coded for each tubing size to assure proper fit and secure, leak-free performance.



SIZES

TUBING DESCRIPTIONS

- FLOPRENE™ Thermoplastic Elastomer (FLO)
- TYGOPRENE XL-60 PVC Based Thermoplastic (TYG)
- NORPRENE¹ Thermoplastic Elastomer (NOR)
- CHEMSURE² Fluoroelastomer (CHE)
- VITON3 Fluoroelastomer (VIT)



² Registered Trademark of W.L. Gore & Associates

FLOPRENE TUBING - 50 Ft Length (Santoprene)

 FLO.016.024 1.6mm (1/16") bore 100 PSI max
--

[■] FLO.032.024 3.2mm (1/8") bore 100 PSI max

CONNECTORS / ADAPTORS

- 1/2" NPTM x pump tubing (bore as required)
- 3/8" PE tubing x pump tubing (bore as required)
- 3/8" and 1/2" PE tubing x 1/2" MNPT
- Two-piece Color Coded Hose Barb & Collar Set. (See back for part number and ordering information)



3/8" PE Tubing Adaptor



1/2" MNPT Tubing Connector



1/2" MPT x 3/8" or 1/2" PE Tubing Connector

³ Registered Trademark of DuPont Performance Elastomers

FLO.048.024 4.8mm (3/16") bore 80 PSI max


[■] FLO.064.024 6.4mm (1/4") bore 60 PSI max

[■] FLO.080.024 8.0mm (5/16") bore 30 PSI max

[■] FLO.096.024 9.6mm (3/8") bore 30 PSI max

FLOMOTION TUBING AND TUBING CONNECTORS SPECIFICATIONS

Peristaltic Pump Tubing Connector / Adapter Ordering Guide



PE Tubing Connectors

038T050NP - 3/8" O.D. Polyethylene Tubing x 1/2" MNPT (PVC) 050T050NP - 1/2" O.D. Polyethylene Tubing x 1/2" MNPT (PVC)

FLOMOTION SYSTEMS Inc.

165 Creekside Drive, Suite 112 Buffalo NY 14228-2103 Tel: 716-691-3941 Fax: 716-691-1253

Email: info@FlomotionSystems.com www.FlomotionSystems.com



