

SUBMITTAL INFORMATION

Uni-Flange[®] Restraint - (UFR1300-C-xx-I style)



SERIES 1300-C 14" - 42" RESTRAINT FOR PVC PIPE AND MECHANICAL JOINT FITTINGS



Noм	PVC PIPE WITH DI PIPE OD		A	B Approx	C Max	Restraining Rods		CLAMPING BOLTS				APPROX.	
Pipe Size	STYLE 1300-C					QTY.	SIZE	QTY.	Size	BC MIN	BC MAX	WT. LBS.	✓ SUBMITTED ITEM(S)
	OD (In.)	CATALOG NO.				-	-				ļ'		(-)
14"	15.30	UFR1300-C-14-I	4"	22-7/16"	15"	6	3/4" x 17"	4	7/8" x 7"	18.50"	20.50"	65	
16"	17.40	UFR1300-C-16-I	4"	24-5/8"	15"	6	3/4" x 17"	4	7/8" x 7"	20.50"	22.50"	68	
18"	19.50	UFR1300-C-18-I	5"	26-7/16"	15"	8	3/4" x 17"	4	1" x 7"	22.75"	24.75"	93	
20"	21.60	UFR1300-C-20-I	5"	29-5/32"	22"	8	3/4" x 24"	4	1-1/8" x 9"	25.00"	27.00"	125	
24"	25.80	UFR1300-C-24-I	5"	33-5/8"	22"	12	3/4" x 24"	4	1-1/8" x 9"	29.50"	31.50"	162	
30"	32.00	UFR1300-C-30-I	7"	40-7/8"	22"	12	1" x 24"	6	1-1/8" x 6"	36.19"	38.19"	250	
36"	38.30	UFR1300-C-36-I	7"	48-1/4"	22"	12	1" x 24"	6	1-1/8" x 6"	42.50"	45.50"	300	
42"	44.50	UFR1300-C-42-I	10-3/4"	57-7/16"	22"	16	1-1/4" x 24"	8	1-1/8" x 6"	49.13"	54.13"	487	

FEATURES

- Cast ductile iron per ASTM A536, grade 65-45-12
- · 360° contact and support of the pipe wall
- · Ideal companion for push-on fittings with restraint ears
- Rods (included) are high strength, low alloy steel ANSI / AWWA C111 / A21.11
- · Clamping bolts and nuts Grade 5, zinc plated
- Rated at full-rated pressure of any class of PVC pipe, minimum 2:1 safety factor
- · Black epoxy coating NSF 61 approved

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc. P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487 Overseas Fax: 260-563-0167 www.fordmeterbox.com

NELANGE 07/28/20

