



SUBMITTAL INFORMATION

Ductile Iron Transition Coupling - (FC2A-xxx-xxx style)



2" & 3" STYLE FC2A COUPLINGS FOR JOINING PIPES WITH THE SAME OR DIFFERENT O.D.'S



NOM. PIPE SIZE	GASKET RANGE 1ST HALF CAT. #	END RING COLOR	BY	GASKET RANGE 2ND HALF CAT. #	END RING COLOR	CENTER SLEEVE		BOLTS		APPROX. OVERALL LGTH.	OAD	APPROX. WT. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
						LGTH.	APPROX. (T) THICKNESS	DIA.	LGTH.					
2"	2.30 - 2.45	Blk	X	2.30 - 2.45	Blk	4"	5/16"	5/8"	6-1/2"	2	5-1/8"	6-1/8"	12	FC2A-245-245
	2.30 - 2.45	Blk		2.40 - 2.65	Blk									FC2A-245-265
	2.30 - 2.45	Blk		2.65 - 2.88	Blk									FC2A-245-288
	2.40 - 2.65	Blk		2.40 - 2.65	Blk									FC2A-265-265
	2.40 - 2.65	Blk		2.65 - 2.88	Blk									FC2A-265-288
	2.65 - 2.88	Blk		2.65 - 2.88	Blk									FC2A-288-288
3"	3.13	Red	X	3.13	Red	4"	3/8"	5/8"	6-1/2"	3	5-1/8"	6-15/16"	18	FC2A-313-313
	3.13	Red		3.45 - 3.60	Red									FC2A-313-360
	3.45 - 3.60	Red		3.45 - 3.60	Red									FC2A-360-360
	3.45 - 3.60	Red		3.70 - 3.88	Blk									FC2A-360-388
	3.45 - 3.60	Red		3.91 - 4.06	Blk									FC2A-360-406
	3.45 - 3.60	Red		4.07 - 4.20	Wht/Gry									FC2A-360-420
	3.70 - 3.88	Blk		3.70 - 3.88	Blk									FC2A-388-388
	3.70 - 3.88	Blk		3.91 - 4.06	Blk									FC2A-388-406
	3.70 - 3.88	Blk		4.07 - 4.20	Wht/Gry									FC2A-388-420
	3.91 - 4.06	Blk		3.91 - 4.06	Blk									FC2A-406-406
	3.91 - 4.06	Blk		4.07 - 4.20	Wht/Gry									FC2A-406-420
	4.07 - 4.20	Wht/Gry		4.07 - 4.20	Wht/Gry									FC2A-420-420

Note: Flexible couplings do not restrain axial forces on piping.

FEATURES

- Center Sleeve: Ductile iron per ASTM A536 (65-45-12)
- End Rings: Ductile iron per ASTM A536 (65-45-12)
- Bolts and Nuts: High strength low alloy steel per ASTM A242 or AWWA C111
- Coating: Black alkyl enamel shop coat - NSF 61 Approved
- Gasket: Molded SBR rubber per ASTM D2000
- NSF61: NSF 61 approved
- Complies with AWWA C219 standards

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
 P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
 Phone: 260-563-3171 / Fax: 800-826-3487
 Overseas Fax: 260-563-0167
 www.fordmeterbox.com

04/27/18

Submitted By:



36 Hudson Rd
 Sudbury MA 01776



800-225-4616
 www.tisales.com